




# Redfish Model for an Ethernet Switch Phase 3

DMTF Redfish Forum



## Using Redfish to manage the Network devices


- ✓ **Compute** - the DMTF released models to manage the compute platform and service
- ✓ **Storage** - SNIA released models to manage networked storage and storage services
- **Network**
  - YANG modules represent the consensus of networking industry experts
  - Convert YANG modules to Redfish schema to leverage this expertise
  - Focus on YANG modules to manage an Ethernet switch





## Tactic - Convert YANG modules to Redfish CSDL


- Phase 1 - DSP-IS00004 v0.9 WIP
  - Converted IETF YANG modules - manage a network device
  - Created mockups by hand
- Phase 2 - DSP-IS00004 v0.9b WIP
  - Converted OpenConfig YANG modules - manage an Ethernet Switch
  - Minor edits to CSDL for converter issues
  - Auto-generated mockup structures
- Phase 3
  - Convert OpenConfig YANG modules
  - Auto-generate mockup structures
  - Propose - WIP release as DSP-IS00004 v0.9c



CSDL = Common Schema Definition Language  
Mapping Spec - <https://www.dmtf.org/dsp/DSP0271>




## Converting YANG module to metadata and mockups





## Managing an Ethernet Switch


- The EthernetSwitch is a type NetworkDevice resource.
- The NetworkDevice resource is the attachment point for the resources mapped from the YANG modules






# The NetworkDevice Resource - openconfig\_acl & openconfig\_interfaces

-  Collection resource
-  Singleton resource






# The NetworkDevice Resource - openconfig\_lacp, \_lldp & \_local\_routing






# The NetworkDevice Resource - openconfig\_network\_instance





# The NetworkDevice Resource - openconfig\_qos





## Contents of Work-in-Progress

### `./mockups/public-ethernet-switch-openconfig`

`./Chassis/EthernetSwitch_15`

`./Managers/EthernetSwitchManager`

`./NetworkDevices/SW_15`

`./NetworkDevices/SW_16`

`./NetworkDevices/SW_17`

### `./metadata`

`RedfishYangExtension_v1.xml`

`openconfig_acl_v1.xml`

`openconfig_interfaces_v1.xml`

`openconfig_lacp_v1.xml`

`openconfig_lldp_v1.xml`

`openconfig_local_routing_v1.xml`

`openconfig_network_instance_v1.xml`

`openconfig_qos_v1.xml`

`openconfig_vlan_v1.xml`

`ietf_inet_types_v1.xml`

`ietf_yang_types_v1.xml`

`minimal_v1.xml`

`minimal_base_v1.xml`

`openconfig_extensions_v1.xml`

`openconfig_inet_types_v1.xml`

`openconfig_network_instance_types_v1.xml`

`openconfig_policy_types_v1.xml`

`openconfig_types_v1.xml`

`openconfig_vlan_types_v1.xml`

`openconfig_yang_types_v1.xml`




## Generating Mockup Files

- Generate binding file

```
$ pyang -f pybind -o binding_interfaces.py openconfig-interfaces.yang
```

- Create python file - genjson-interface.py



```
import pyangbind.lib.pybindJSON as pybindJSON
from binding_interfaces import openconfig_interfaces
oclr = openconfig_interfaces()
print(pybindJSON.dumps(oclr, filter=False))
```

'filter=False' means display empty properties

- Execute python file

```
$ python genjson-interfaces.py
```

```
{
  "name": "",
  "interfaces": {
    "interface": {}
  }
  ...
}
```



## Example ../openconfig\_interfaces/interfaces/TenGig\_2

- Edit genjson-interfaces.py

```
import pyangbind.lib.pybindJSON as pybindJSON
from binding_interfaces import openconfig_interfaces
oclr = openconfig_interfaces()
rt = oclr.interfaces.interface.add("TenGig_2")
print(pybindJSON.dumps(oclr, filter=False))
```

- Execute

```
$ python genjson-interfaces.py ————— output —————>
```

```
{
  "name": "TenGig_2",
  "state": {
    "name": "",
    "type": "",
    "loopback-mode": false,
    "ifindex": 0,
    "mtu": 0,
    "oper-status": "",
    "enabled": 1,
    "counters": {
      "in-discards": 0,
      "out-unicast-pkts": 0,
      "in-unknown-protos": 0,
      "carrier-transitions": 0,
      ...
    }
  },
  "subinterfaces": {
    "subinterface": {}
  },
  "config": {
    "type": "",
    "loopback-mode": false,
    "name": "",
    "mtu": 0,
    "enabled": 1
  },
  "hold-time": {
    "state": { "down": 0, "up": 0 },
    "config": { "down": 0, "up": 0 }
  }
}
```

- Edit output

- Add Redfish properties
  - @odata properties
  - "Id" property
- Add property values
- Create collection resources



## Additional Documentation

- YANG-to-Redfish Mapping Specification (DMTF work-in-progress)
  - Specifies how to convert a YANG model to a Redfish model
  - [http://www.dmtf.org/sites/default/files/standards/documents/DSP0271\\_0.5.6.pdf](http://www.dmtf.org/sites/default/files/standards/documents/DSP0271_0.5.6.pdf)
- YANG-to-Redfish-Converter
  - Open source repository for converter
  - <https://github.com/DMTF/YANG-to-Redfish-Converter>